

W335

Bright WXGA Projector



Features

- Luminous WXGA projection with 3,800 lumens and 22,000:1 contrast ratio
- HDMI, VGA and composite connectivity
- Up to 15,000-hour lamp life
- Vertical keystone for easy positioning
- Integrated 10-watt speaker



Robust I/O and superior performance

Enhance spaces with captivating 3,800 lumens WXGA images with the Optoma W335. Its 22,000:1 contrast ratio, 1.55 - 1.73:1 throw ratio and 1.1x zoom make it ideal for small-to-medium spaces, such as classrooms, offices and training spaces.

Vertical keystone support simplifies placement for easy installation. An integrated 10-watt speaker delivers crisp, room-filling audio that enhances presentations and videos without any additional equipment.

Robust input options, including HDMI, VGA and composite enable connectivity to a wide range of devices. A 15,000-hour lamp life enables many years of use with minimal maintenance.



W335



TECHNICAL SPECIFICATIONS

| | |
|--------------------------------|---|
| Aspect Ratio | 16:10 |
| Audio | 10W speaker |
| Brightness | 3,800 lumens |
| Compatible Aspect Ratio | 16:10 (native), 16:9 and auto compatible |
| Connections | 1 x HDMI v1.4a, 1 x VGA, 1 x composite, 1 x audio-in, 1 x USB-A (5v / 1.0 amp), 1 x VGA, 1 x audio, 1 x RS232 |
| Contrast Ratio | 22,000:1 |
| Display Technology | Texas Instruments 0.65" WXGA DMD |
| Displayable Colors | 1.07 billion |
| Keystone Correction | ± 40° Vertical |
| Light Source Type | 203W |
| Light Source Life | 15,000/12,000/10,000/6,000 (Eco+/Dynamic/Eco/Bright) |
| Lens Shift | None |
| Maximum Resolution | WUXGA (1920 x 1200) |
| Native Resolution | WXGA (1280 x 800) |
| Noise Level | 27dB |
| Offset | 115% ± 5% |
| On-Screen Display | Complete on-screen menu adjustments in 26 languages |
| Operating Temperature | Sea Level to 10,000 feet (@73°F); must manually switch to high-altitude mode at 5,000 feet & above |
| Power Consumption | 230W (Bright) / 190W (Eco) |
| Power Supply | AC input 100-240V, 50-60Hz, auto-switching |

| | |
|-------------------------------|-----------------------------|
| Projection Distance | 3.9' - 45.9' (without zoom) |
| Projection Lens | F=2.41~2.53, F=21.85~24 mm |
| Projection Screen Size | 29.7" - 300.7" |
| Remote Control | IR remote control |
| Throw Ratio | 1.55 - 1.73:1 |

COMPATIBILITY SPECIFICATIONS

| | |
|-------------------------------|---|
| 3D Compatibility | Side-by-Side: 1080i50 / 60, 720p50 / 60, Frame-pack: 1080p24, 720p50 / 60, Over-Under: 1080p24, 720p50 / 60 |
| Computer Compatibility | WUXGA, UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA resized, VESA, PC and Mac |
| Connections | 1 x HDMI v1.4a, 1 x VGA, 1 x composite, 1 x audio-in, 1 x USB-A (5v / 1.0 amp), 1 x VGA, 1 x audio, 1 x RS232 |
| Horizontal Scan Rate | 15.3 - 91.1kHz |
| RoHS | Compliant |
| Vertical Scan Rate | 50-85 Hz (120Hz for 3D feature projector) |
| Video Compatibility | HDTV (720p, 1080i/p), SDTV (480i/p, 576i/p) |

PHYSICAL SPECIFICATIONS

| | |
|-------------------------------|---|
| Dimensions (W x H x D) | 12.4" x 3.9" x 9.6" |
| Security | Security bar, Kensington lock, password protection, keypad lock |
| Weight | 6.7 lbs. |

Other

What's in the Box? W335, AC power cable, remote control, batteries, quick start user manual

Accessories 4K UHD Casting and Mirror Dongle: UHDCast Pro Carrying case: BK-4028 Lamp (replacement): BL-FU200D QuickCast Pro 4K HDMI starter kit: QCP-4K-KIT (2 TX, 1 RX, 1

Part Numbers Cradle) QuickCast Pro 4K HDMI starter kit: QCP-SK-4K-HDMI (1 TX and 1 RX) Remote (replacement): 45.71P01G002 Universal ceiling mount: BM-5001U Universal Ceiling mount: OCM815W Universal Ceiling mount: OCM818W-RU

*Lamp life is dependent upon many factors, including lamp mode, display mode, usage, environmental conditions and more. Lamp brightness can decrease over time.

† 3D content can be viewed with DLP® Link active shutter glasses when projector is used with a compatible 3D player. Please visit Optoma.com for more information.

Optoma.com

Copyright © 2018 Optoma Technology, Inc. DLP® and the DLP logo are registered trademarks of Texas Instruments™. All other trademarks are the property of their respective owners. All specifications subject to change.

Published on 05/29/20